

ClearComm

- Provides ● clear speech through fixed glass screens
● speech enhancement for hearing aid users



ClearComm VF Speech Transfer

ClearComm Speech Transfer provides full, hands-free, 2-way speech transfer between staff and public. Both staff and public positions are equipped with microphone and loudspeakers linked by a two-channel audio amplifier.

Each system is supplied with its own power supply unit, plugged into a standard, 3-pin, electrical socket.

Convenient, simple, staff amplifier controls allow the user to adjust the volume to mute either direction of sound transfer and to turn the system off or on.

All system components are connected using a simple "plug and socket" for a neat, unobtrusive and simple installation. This allows simple component replacement in the event of equipment failure.

Installation can be surface mounted or recessed into the counter.

Staff are normally equipped with a goose-neck microphone mounted on the loudspeaker pod.

Public microphones can be integrated into speaker pods or in the flush mounted speaker grilles on either side of the transaction point or mounted on a bridge bar set between the speaker pods.

Close-coupled microphones ensure that background noise is kept to a minimum.

Standard finishes are black or grey.

Introduction

Fixed screens and background noise levels make communication difficult. ClearComm Speech Transfer and Induction Loop Systems enhance customer service by improving clarity and audibility, avoiding raised voices and maintaining privacy.

ClearComm is available as a microphone/speaker set with an optional induction loop or as an induction loop only.



Bridge Bar Configuration



Flush Mounted Configuration



Surface Mounted Configuration

